



NOTES: 1) ALL DIMENSIONS ARE IN mm WITH CONVERSION FOR (INCHES).  
 2) CMA ACTUATORS CAN BE SELECTED WITH EITHER METRIC OR IMPERIAL SIZES FOR THE SHAFT AND CONDUIT ENTRY. THESE ARE NOT SIMPLE CONVERSIONS BUT DIFFERENT DIMENSIONS.

DIMENSIONS WITH ' \* ' INDICATE COVER REMOVAL ALLOWANCE.

THE INTERFACE PROVIDED FOR MOUNTING THE ACTUATOR ON TO THE VALVE SHOULD CONFORM TO GOOD ENGINEERING PRACTICES, ENSURING ADEQUATE TOLERANCES, THREAD ENGAGEMENT, SCREW TORQUES, SIZES, MATERIALS & FORM TOLERANCES.

UNIT WEIGHT - 23.1 lbs (10.5 Kg)

<b>TOLERANCES</b> DIMENSIONS IN MILLIMETERS UNLESS OTHERWISE SPECIFIED X = ±.5mm .XX = ±.1mm ANGULAR ±1°			 MILWAUKEE, WISCONSIN, USA	TITLE: CMA INSTALLATION DRAWING	
SCALE: 1:2				FOR: CMR-50 CMR-100 CMR-200 LONG COVER	
DRAWN: RLY	PROD. DV:	PROD. ENG: RLY	This print is the property of Rotork Process Controls and is loaned in confidence subject to return. All rights to design or invention are reserved.		
DATE: 4/7/16	DATE:	DATE: 12/13/13	96	C	048319