

Portafuse 4 Lite

LITHIUM BATTERY ELECTROFUSION MACHINE

PORTAFUSE 4 LITE IS THE NEXT GENERATION OF THE PORTAFUSE LINE OF MACHINES BROUGHT TO YOU BY KEROTEST. THE UPGRADED POWER PACK USES LITHIUM POWER TECHNOLOGY TO LOWER WEIGHT AND INCREASE THIS TRUSTED TOOL'S RELIABILITY. PORTAFUSE LIGHT IS IDEALLY SUITED TO NG UTILITY SERVICE AND LIGHT OPERATION APPLICATIONS.

FEATURES

• FUSES COUPLINGS UP TO 4 IPS, **ALL SADDLE & TAPPING TEES**

 FULL SERVICE & CALIBRATION BY **KEROTEST & KEROTEST AGENT**

• FULL TRACEABILITY

ISO 12176-2 COMPLIANT

10000 FUSION REPORTS

LIGHT WEIGHT 26.5 LBS

• IMPACT RESISTANT CASE

GPS

BARCODE SCANNER READER

BLUETOOTH

SPECIFICATIONS

| Part No: 72771004 | Power: 5Ah Lithium-ion | Traceability: Fusion, operator, location, fitting |
|--|--|--|
| Compatibility: Couplings up to 6 IPS and all saddle and tapping tees | ISO barcode: 24: Electrofusion - ISO 13950 30: Operator - ISO 12176-2 | Temperature Range: 0°F to 120°F |
| Input voltage: 110V / 50-60 Hz | ASTM barcode: Fitting Traceability - ASTM F2897 | Protection: IP54 |
| Output voltage: 8-48V | Mode: Barcode / Manual | USB port: Yes |

FORM FACTOR

Impact resistant case

12ft output cable, barcode scanner reader, set of 4mm, 4.7mm or universal tip

adaptors

2024.07.01

Dimensions: 18.27" x 14.41" x 6.93"

Weight: 26.5 lbs

Kerotest Manufacturing Corp. 5500 Second Avenue Pittsburgh, PA 15207 Phone: 412-521-4200 Sales@Kerotest.com