

Portafuse 4 Max LITHIUM BATTERY ELECTROFUSION MACHINE

PORTAFUSE 4 MAX TAKES THE PORTAFUSE LINE OF MACHINES BROUGHT TO YOU BY KEROTEST TO A NEW LEVEL. THE LITHIUM-ION 32 AMP HOUR POWERPACK IS DESIGNED TO FULFILL ALL TYPICAL GAS UTILITY APPLICATIONS WITHOUT GENERATORS AND EXTENSION CORDS.

FEATURES

• FUSES COUPLINGS UP TO 12 IPS, **ALL SADDLE & TAPPING TEES**

 FULL SERVICE & CALIBRATION BY **KEROTEST & KEROTEST AGENT**

• FULL TRACEABILITY

ISO 12176-2 COMPLIANT

10000 FUSION REPORTS

44 LBS

• IMPACT RESISTANT CASE

GPS

BARCODE SCANNER READER

BLUETOOTH

SPECIFICATIONS

Part No: 72771012	Power: 32Ah Lithium-ion	Traceability: Fusion, operator, location, fitting
Compatibility: Couplings up to 12 IPS and all saddle and tapping tees	ISO barcode: 24: Electrofusion - ISO 13950 30: Operator - ISO 12176-2	Temperature Range: 0°F to 120°F
Input voltage: 110V / 50-60 Hz	ASTM barcode: Fitting Traceability - ASTM F2897	Protection: IP54
Output voltage: 8-48V	Mode: Barcode / Manual	USB port: Yes

FORM FACTOR

Impact resistant case

12ft output cable, barcode scanner reader, set of 4mm, 4.7mm or universal tip

adaptors

2024.07.01

Dimensions: 18.27" x 14.41" x 6.93"

Weight: 44 lbs

Kerotest Manufacturing Corp. 5500 Second Avenue Pittsburgh, PA 15207 Phone: 412-521-4200 Sales@Kerotest.com